



UPower Pro-43

4-Slot Hot Swappable Battery Medical Power Bank



Features

- Compatible with onyx XL battery and XXL battery (not for STD battery)
- Two mode for user
 - Normal mode : max capacity – 90W/520Wh (with XXL battery)
 - Power mode : max output – 90W/260Wh + 65W/260Wh (with XXL battery)
- 3x DC output
- Selectable voltage for output 1/2 (12V / 15V / 19V / 24V)
- Built-in wifi chip for remote monitor directly
- LED indicator, clearly reveal recharge/discharge status

Specifications

MAIN SPECIFICATIONS

	UP-43P (Power Bank)	UP-43L (Charger only)
Output Voltage	DC out x3 Selectable voltage for output 1/2 12/15/19/24V (only one voltage at the same time for one port)	N/A
Output Capacity	Normal mode : share 90W with 2 port Power mode : 90W for ch1; 65W for ch2 Medical 45W AC output (optional)	N/A
Charge Time	6hrs for XL battery; 8hrs for XXL battery (no charge when power output)	Normal Charge: 8hrs for XL battery; 10hrs for XXL battery Fast Charge: 3.5hrs for XL
Function Key	Power Mode Button : Normal(max capacity) Power mode(max output) Charge Button : Power output charger	Fast Charge Button : normal charge fast charge
Extend Function	Adaptor holder (optional) Cart mount bracket (optional) UP board (optional) 45W Medical AC inverter (optional)	Adaptor holder (optional) Cart mount bracket (optional)
Safety	Supports protection from over-voltage (input), over-current (input and output), short circuit, over-charge.	
Certification	CE, FCC, IEC60601-1	

MECHANICAL AND ENVIRONMENTAL

Architecture	ABS + PC
Color	White
Dimension	255(L) x 160(W) x 213(H) mm
Net Weight	1kg (1.47 lbs) (w/o battery)
Operating Temperature	0°C ~ 35°C(32°F ~ 95°F)
Storage Temperature	-20°C ~ 60°C(-4°F ~ 140°F)
Storage Humidity	10%~95%@35°C, non-condensing

POWER SUPPLY SPECIFICATION

Input Voltage	100-240V AC @50-60 Hz
Output Power	24V / 250W max

Ordering Information

- **UP-43P-A1-1010 (Power Bank)**
4-slot Power Bank.12/15/19/24V DC output.24V/250W
- **UP-43L-A1-1010 (Charger only)**
4-slot Charger.24V/250W adaptor
- **9789BAXL14**
8400mAh/10.9V battery x2
- **OPM-P03T-03**
12060mAh/10.8V battery x2